

YANTON®

500 Channels 10 Watt. OLED HD Display

MAIN FEATURE

Single Band, Dual standby, Dual display
PTT ID
AB Channel Function Operate Separately
Scrambler
Double PTT

T-890 PROFESSIONAL FM TRANSCEIVER



YANTON®

T-890 PROFESSIONAL FM TRANSCEIVER

STANDARD ACCESSORIES



SPECIFICATION

| GENERAL | |
|-----------------------------|--|
| Frequency Range | VHF: 136-174MHz or 220-260MHz UHF: 400-480MHz or 450-520MHz |
| Operating Temperature | -20°C to +55°C |
| Frequency Combination | please lock frequency synthesize |
| Frequency Stability | ±2.5ppm |
| Memory Channel | 2*250 |
| Working voltage | 7.4V |
| Antenna Impedance | 50Ω |
| Operating Mode | simplex of co-frequency or alien |
| Dimensions | 124*45*35mm(without antenna) |
| Weight | 260g |
| TRANSMITTER | |
| RF power | 10W |
| Modulate Mode | F3E |
| Max.Freq.Deviation | ±5KHz |
| Remain Wave Radiation | <-60dB |
| Transmitting Current | ≤1000mA |
| RECEIVER | |
| Sensitivity | <0.20uV [12dB SINAD] |
| Squeich Sensitivity | <0.20uV |
| Intermodulation Antijamming | 50dB |
| Audio Power output | 500mW |
| Receiving Current | ≤100mA |
| Squelch Stangby | 20mA |
| Audio response | =1dB~-3dB |
| Rated audio distortion | 3%(Type) |

MAIN FEATURES

500 Channels
10 Watt.
OLED HD Display

Single Band, Dual standby, Dual display
PTT ID
AB Channel Function Operate Separately
Scrambler
Double PTT